

## DC-Servomotor KN 12 M4 inch version

### Characteristics

<b>Rated Values</b> <sup>1</sup>			
Nominal torque	$M_N$	136	Ncm
Nominal speed <sup>2</sup>	$n_N$	3000	min <sup>-1</sup>
Nominal output <sup>2</sup>	$P_N$	426	W
Terminal voltage	$U_N$	46	V
Nominal current	$I_N$	9,2	A

<b>Motor Performance</b>			
Peak torque <sup>3</sup>	$M_{max}$	1438	Ncm
Max. peak current <sup>3</sup>	$I_{max}$	92	A
Acceleration at peak torque	$a_{max}$	107	10 <sup>3</sup> rad/s <sup>2</sup>
Stall torque <sup>4</sup>	$M_0$	124	Ncm
Current at stall torque <sup>4</sup>	$I_0$	8,8	A
Max. load speed	$n_{max}$	5000	min <sup>-1</sup>
Max. no load speed	$n_0$	6000	min <sup>-1</sup>

<b>Thermal Characteristics</b>			
Time const. armature-housing	$T_{th1}$	1	min
Time const. housing-ambient <sup>5</sup>	$T_{th2}$	32	min
Resistance armature-housing	$R_{th1}$	1,6	K/W
Resistance housing-ambient <sup>5</sup>	$R_{th2}$	1,2	K/W
Temp.- coeff. of back EMF	$c_{th}$	-0,11	%/K
Max. cont. armature temp.	th	155	°C

<b>Physical Data</b>			
Number of magnet poles	$2p$	8	pcs
Number of commutator bars	$z$	141	pcs
Admitted shaft load, radial	$F_R$	220	N
Admitted shaft load, axial	$F_A$	180	N
Weight without extensions	$m$	2,8	kg

<b>Intrinsic Motor Constants</b>			
Torque constant	$k_T$	14,0	Ncm/A
Back E.M.F constant	$k_E$	14,7	V/10 <sup>3</sup> min <sup>-1</sup>
Viscous damping constant	$k_D$	1,9	Ncm/10 <sup>3</sup> min <sup>-1</sup>
Speed regulation at const. Voltage	$k_n$	4,44	min <sup>-1</sup> /Ncm
Average friction torque	$M_F$	3,7	Ncm
Terminal resistance (+25 °C)	$R_A$	0,75	?
Armature (Cu) resistance (+25 °C)	$R_{Cu}$	0,61	?
Armature Inductance (10 <sup>3</sup> Hz)	$L_A$	<0,05	mH
Mechanical time constant	$T_m$	4,5	ms
Electrical time constant	$T_e$	<0,07	ms
Rotor inertia	$J$	1,343	kg cm <sup>2</sup>

<sup>1)</sup> for DC current with formfactor 1,05, uncooled execution, protection IP 54, ambient temperature +40 °C.

<sup>2)</sup> Continuous operation S1 (VDE 530), part 1,4. Motor can be run at all points of the torque speed curve S1, continuous speed beyond 4000 min<sup>-1</sup> is not recommended, please check the torque speed curve.

<sup>3)</sup> Incremental motion cycle S3, VDE 530, part 1,4. Pulse duration 50 ms, 1% of duty cycle.

<sup>4)</sup> Point of intersection torque speed curve S1 with torque coordinate at speed zero. Permitted at very low speed < 1min<sup>-1</sup>. Works the motor with blocked shaft longer than 20 s, the stall current must be reduced to appr. 70%.

<sup>5)</sup> Based upon mounted motors, heat transfer from motor to equipment.

Outline dimensions motor (in mm):

